



ATAM Zwillingssystem

TYP: ATAM		180 ZW	300 ZW	450 ZW	700 ZW	900 ZW	1.200 ZW	1.500 ZW	2.100 ZW
LEISTUNG	l/h	180	300	450	700	900	1.200	1.500	2.100
SPANNUNG MOTOR- LEISTUNG	V	400	400	400	400	400	400	400	400
	kW	0,25	0,25	0,25	0,33	0,55	0,55	0,55	1
UMDREHUNGEN MOTOR	U/min ⁻¹	1.400	1.400	1.400	1.400	1.400	1.400	1.400	1.400
ANSCHLÜSSE	SAUGSEITE	1/2" iG	1/2" iG	1/2" iG	3/4" iG	3/4" iG	3/4" iG	1" iG	1" iG
	DRUCKSEITE	1/2" iG	1/2" iG	1/2" iG	3/4" iG	3/4" iG	3/4" iG	1" iG	1" iG
	ÜBERDRUCKSEITE	1/2" iG	1/2" iG	1/2" iG	3/4" iG	3/4" iG	3/4" iG	1" iG	1" iG
SICHERHEITSVENTIL ÖFFNUNG	bar	4,5	4,5	4,5	4,5	4,5	4,5	4,5	4,5
GERÄUSCHPEGEL	dB (A)	58	58	58	58	58	58	58	58
MOTOR- SCHUTZART	IP	55	55	55	55	55	55	55	55

- Das Aggregat ist nach DIN 12.514-1 gebaut und geprüft.

typ	ATAM 180 ZW	ATAM 300 ZW	ATAM 450 ZW	ATAM 700 ZW	ATAM 900 ZW	ATAM 1.200 ZW	ATAM 1.500 ZW	ATAM 2.100 ZW
A	700	700	700	800	890	890	1.115	1.115
B	550	550	550	720	750	750	970	970
C	300	300	300	350	400	400	500	500
GEWICHT ca. (kg)	31	34	34	65	80	90	150	160

